

### Features and Components


#### DynaTred™, DynaTred Plus®, and DynaTred Max™

Preformed, skid-resistant roof protection pads consisting of modified asphalt, reinforcements and fillers with a ceramic granule surface on both sides. They are durable, resilient and maintenance free.

DynaTred, DynaTred Plus and DynaTred Max can be installed over built-up and modified bitumen roofing systems to provide an integral, skid-resistant walkway for demanding service access needs.

**Ceramic-Coated Roofing Granules:** Specifically engineered for optimal embedment in the modified asphalt sheet. The ceramic coating promotes excellent long-term adhesion.

**Easy Installation:** Can be easily cut with a heavy-duty utility knife or circular saw with a carbide-tipped blade.



Component

**M**  
Membrane

Multi-Ply

Type

**PT**  
Protection

### System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS			
	HA	CA	CA	HW	HA	CA	HW	SA
			C					

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
			D				

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened FA = Fully Adhered BA = Ballasted

### Energy and the Environment
