



**SECTIONAL PIPE INSULATION - SINGLE LAYER**

Description	Quantity	Unit	Material	Notes

## SECTIONAL PIPE INSULATION - SINGLE LAYER, continued






## SECTIONAL PIPE INSULATION - SINGLE LAYER, continued

I.D. Pipe Size (in) (mm)		5" Thick				5½" Thick				6" Thick			
		Ln.Ft./ Carton	Load Factor	Cube/ Carton	Lbs./ Carton	Ln.Ft./ Carton	Load Factor	Cube/ Carton	Lbs./ Carton	Ln.Ft./ Carton	Load Factor	Cube/ Carton	Lbs./ Carton
½	15	-	-	-	-	-	-	-	-	-	-	-	-
¾	20	-	-	-	-	-	-	-	-	-	-	-	-
1	25	-	-	-	-	-	-	-	-	-	-	-	-
1¼	32	-	-	-	-	-	-	-	-	-	-	-	-
1½	40	-	-	-	-	-	-	-	-	-	-	-	-
2	50	-	-	-	-	-	-	-	-	-	-	-	-
2½	65	-	-	-	-	-	-	-	-	-	-	-	-
3	80	-	-	-	-	-	-	-	-	-	-	-	-
3½	90	-	-	-	-	-	-	-	-	-	-	-	-
4	100	-	-	-	-	-	-	-	-	-	-	-	-
4½	115	-	-	-	-	-	-	-	-	-	-	-	-
5	125	-	-	-	-	-	-	-	-	-	-	-	-
6	150	3	0.161	6.08	32	3	0.161	6.08	36	3	0.183	6.59	39
7	175	3	0.161	6.08	33	3	0.183	6.59	35	3	0.160	5.78	45
8	200	3	0.183	6.59	42	3	0.231	7.14	45	3	0.247	7.98	44
9	225	3	0.231	7.14	41	3	0.247	7.98	43	3	0.265	9.19	44
10	250	3	0.247	7.98	41	3	0.265	9.19	45	3	0.265	9.19	49
11	275	3	0.265	9.19	45	3	0.265	9.19	47	3	0.266	9.51	48
12	300	3	0.265	9.19	47	3	0.266	9.51	49	3	0.285	10.48	51
14	350	3	0.266	9.51	49	3	0.290	11.30	49	1.5	0.247	7.98	30
15	375	3	0.290	11.30	48	1.5	0.247	7.98	30	1.5	0.264	8.87	30
16	400	1.5	0.247	7.98	27	1.5	0.264	8.87	31	1.5	0.265	9.19	31
17	425	1.5	0.264	8.87	29	1.5	0.265	9.19	32	1.5	0.266	9.51	33
18	450	1.5	0.265	9.19	28	1.5	0.266	9.51	31	1.5	0.285	10.48	35
19	475	1.5	0.266	9.51	31	1.5	0.285	10.48	32	1.5	0.161	6.08	35
20	500	1.5	0.285	10.48	34	1.5	0.161	6.08	36	1.5	0.161	6.08	36
21	525	1.5	0.161	6.08	33	1.5	0.161	6.08	34	1.5	0.161	6.08	37
22	550	1.5	0.161	6.08	34	1.5	0.161	6.08	35	1.5	0.183	6.59	38
23	575	1.5	0.161	6.08	35	1.5	0.183	6.59	36	1.5	0.231	7.14	40
24	600	1.5	0.183	6.59	36	1.5	0.231	7.14	38	1.5	0.231	7.14	42



## SECTIONAL PIPE INSULATION - QUAD, continued



Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The physical and chemical properties of the products listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Any references to numerical flame spread or smoke developed ratings are not intended to reflect hazards presented by these or any other materials under actual fire conditions. Check with the Regional Sales Office nearest you for current information.

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville thermal insulation and systems, visit [www.jm.com/terms-conditions](http://www.jm.com/terms-conditions) or call (800)654-3103.