

APPLICATION

$\frac{3}{4}$ " X .020" stainless steel strapping is slipped through and back over the slots on one end of the flat bottom of the spring. Strapping is secured with a $\frac{3}{4}$ " closed seal. Strapping is extended around the object, or to the next spring, and the routine is repeated until the entire circumference has been encircled. (Secure the SUPER MITY-SPRING with $\frac{1}{4}$ " X .020" strapping, and $\frac{1}{4}$ " closed seals.)

To accommodate expected expansion of the object, the number of MITY-SPRING compression springs to be installed is based on a maximum compression of $\frac{1}{2}$ " per MITY-SPRING or SUPER MITY-SPRING.

Install one MITY-SPRING compression spring for every 25' of strapping. When tensioning the strapping, compress each spring unit a total of $\frac{1}{2}$ " ($\frac{1}{4}$ " for each half of the spring unit). Extreme care should be taken to assure that spring compression and strapping stresses are evenly distributed around the object.

Formerly Pabco/Childers Metals



717 17th St.
Denver, CO 80202
(800) 866-3234
JM.com

Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The physical and chemical properties of the product listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Any references to numerical flame spread or smoke developed ratings are not intended to reflect hazards presented by these or any other materials under actual fire conditions. Check with the Regional Sales Office nearest you for current information.

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville thermal insulation and systems, visit www.jm.com/terms-conditions or call (800)654-3103.